

TECHNICAL DATA

CLASSIFICATION

Heavy-duty class 8, Type-D

GVWR

42,990 lbs.

PAYLOAD CAPACITY * 13,790 lbs.

AXLE WEIGHT LOAD RATING Front: 14,330 lbs., Rear: 24,250 lbs.

LENGTH 40 feet

WHEELBASE 240.15 inches

OVERHANG 104.5 (front), 127.8 inches (rear)

APPROACH & DEPARTURE ANGLES 6 8 (front), 8 degrees (rear) WIDTH

102 inches, widest in the industry 2

HEIGHT * 138.5 inches

TIRES

295 / 80R / 22.5 (qty. 6)

TURNING RADIUS 41.3 feet (outside body)

SUSPENSION Air ride suspension

PASSENGER DOOR Electric, 36 wide, 34-inch opening

EMERGENCY EXITS

Hatch, window, door ADA

Yes

HVAC

75,000 BTU/h, front, rear, electric

ECU COMMUNICATION **CAN BUS, J1939**

CHP CERTIFIED

BUY AMERICA *



BEAST

SEATING CONFIGURATION * (7) Front facing bench seating, 15 rows, 2 benches per row, 3 seats per bench MAX SEATING CAPACITY (w/driver) 91 seating

STORAGE Full pass-through storage compartment BATTERY

Voltage: 614 V, Chemistry: LiFePo4

BATTERY CAPACITY 194 kWh, 6 total packs

RANGE * 140 miles

FUEL ECONOMY * 23 mpge, 1.5 kWh/mi, 0.67 mi/kWh TOP SPEED

68 mph

MOTOR POWER 350 kW max

TRANSMISSION Direct Drive, No Transmission

BRAKES Full ABS Disc Brakes

FRAME / BODY / ROOF Steel, Monocoque

DESIGN LIFE 10 years

LCFS EER VALUE * † HDV, 5.0 EER, 1 credit every 740 kWh

CHARGING * (AC/DC)

LEVEL-2, J1772 19 kW, 220 V, 10.5 hrs

DCFC, CCS-1 61 kW, 3.25 hrs

WIRELESS DC * (option) 60 kW, 3.50 hrs


VEHICLE VOUCHER REBATES * E-mail: grants@greenpowermotor.com

CARB CERTIFIED

† California region only

* Specification can vary By region, application, availability

LAYOUT DIMENSIONS & SEATING



driver (Y